

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard
 29 CFR 1910.1299 Standard must be
 consulted for specific requirements

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

SECTION I

IDENTITY: CONCRETE MASONRY PRODUCTS (BLOCK, LINTELS, PAVERS)

MANUFACTURER'S NAME	EMERGENCY TELEPHONE NUMBER
OLDCASTLE APG SOUTH, INC. OR AFFILIATED COMPANY	678-461-2830
STREET ADDRESS	TELEPHONE NUMBER FOR INFORMATION
3700 MANSELL RD, SUITE # 250	678-461-2830
CITY/STATE/ZIP	DATE PREPARED
ALPHARETTA, GA 30022	03-04

SECTION II HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS: SILICA, CRYSTALLINE QUARTZ (RESPIRABLE)
 SPECIFIC CHEMICAL IDENTITY: SILICON DIOXIDE (SiO₂, CAS 14808-60-7)
 COMMON NAMES: SILICA, FLINT, SAND, CRYSTALLINE FREE SAND, QUARTZ, GROUND SILICA, SILICA FLOUR
 OSHA PEL: EXPOSURE TO AIRBORNE CRYSTALLINE SILICA SHALL NOT EXCEED AN 8-HOUR TIME-WEIGHTED AVERAGE LIMIT AS STATED IN 29-CFR 1910.1000 TABLE Z - 1 - A, AIR CONTAMINANTS, SPECIFICALLY SILICA, CRYSTALLINE QUARTZ (RESPIRABLE DUST) 0.1 mg/M³
 ACGIH TLV: CRYSTALLINE QUARTZ, TLV - TWA = 0.1 mg/M³ (RESPIRABLE DUST), SEE THRESHOLD LIMIT VALUE AND BIOLOGICAL EXPOSURES INDICES FOR 1991-1992, AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS
 OTHER LIMITS RECOMMENDED: NATIONAL INSTITUTE FOR OCCUPATIONAL SAFETY AND HEALTH (NIOSH): RECOMMENDED STANDARD WORKING PERMISSIBLE CONCENTRATION: = 0.05 mg/M³ (RESPIRABLE FREE SILICA) AS DETERMINED BY A FULL-SHIFT SAMPLE UP TO A 10-HOUR WORK DAY, 40-HOUR WORK WEEK.
 SEE NIOSH CRITERIA FOR A RECOMMENDED STANDARD OCCUPATIONAL EXPOSURE TO CRYSTALLINE SILICA.

SECTION III- PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT	N/A	SPECIFIC GRAVITY (H ₂ O = 1)	N/A
VAPOR PRESSURE (MM Hg.)	N/A	MELTING POINT	N/A
VAPOR DENSITY (AIR = 1)	N/A	EVAPORATION RATE (BUTYL ACETATE = 1)	N/A
SOLUBILITY IN WATER	APPEARANCE AND ODOR		
NOT SOLUBLE	ODORLESS		

SECTION IV HEALTH HAZARD DATA

FLASH POINT (METHOD USED)	N/A	FLAMMABLE LIMITS	N/A	LEL	N/A	UEL	N/A
EXTINGUISHING MEDIA	N/A	SPECIAL FIREFIGHTING PROCEDURES	NONE	UNUSUAL FIRE AND EXPLOSION HAZARDS	NONE		

SECTION V- REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	✓	NONE

INCOMPATIBILITY (MATERIALS TO AVOID) NONE

HAZARDOUS DECOMPOSITION OR BYPRODUCTS NONE

HAZARDOUS POLYMERIZATION	UNSTABLE		CONDITIONS TO AVOID
	STABLE	✓	NONE

SECTION VI- HEALTH HAZARD DATA

ROUTES OF ENTRY	INHALATION	YES	SKIN	NO	INGESTION	YES
-----------------	------------	-----	------	----	-----------	-----

HEALTH HAZARDS (ACUTE AND CHRONIC):
 DRY SAWING OR GRINDING OF CONCRETE MASONRY PRODUCTS MAY RESULT IN THE RELEASE OF RESPIRABLE CRYSTALLINE QUARTZ. PROLONGED EXPOSURE TO RESPIRABLE CRYSTALLINE QUARTZ MAY CAUSE DELAYED (CHRONIC) LUNG INJURY (SILICOSIS). ACUTE OR RAPIDLY DEVELOPING SILICOSIS MAY OCCUR IN A SHORT PERIOD OF TIME IN HEAVY EXPOSURE. SILICOSIS IS A FORM OF DISABLING PULMONARY FIBROSIS WHICH CAN BE PROGRESSIVE AND MAY LEAD TO DEATH.
 CARCINOGENICITY: NTP? YES.
 THE NATIONAL TOXICOLOGY PROGRAM (NTP) PUBLISHED ITS SIXTH ANNUAL REPORT ON CARCINOGENS WHICH CONCLUDES THAT "SILICA, CRYSTALLINE (RESPIRABLE)" MAY REASONABLY BE ANTICIPATED TO BE A CARCINOGEN. THE NTP CONCLUSION IS BASED ON SUFFICIENT EVIDENCE FOR THE CARCINOGENICITY OF RESPIRABLE CRYSTALLINE SILICA IN EXPERIMENTAL ANIMALS AND LIMITED EVIDENCE IN HUMANS.
 IARC MONOGRAPHS? YES
 IARC MONOGRAPHS ON THE EVALUATION OF THE CARCINOGENIC RISK OF CHEMICALS TO HUMANS (VOL. 42, 1987) CONCLUDES THAT THERE IS SUFFICIENT EVIDENCE FOR THE CARCINOGENICITY OF CRYSTALLINE SILICA TO EXPERIMENTAL ANIMALS AND THAT THERE IS LIMITED EVIDENCE OF THE CARCINOGENICITY OF CRYSTALLINE SILICA TO HUMANS IARC CLASS 2A.

SIGNS AND SYMPTOMS OF EXPOSURE: UNDUE BREATHLESSNESS, WHEEZING, COUGH AND SPUTUM PRODUCTION.
 MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:
 PRE-EXISTING LUNG SUCH AS EMPHYSEMA OR ASTHMA, PULMONARY FUNCTION MAY BE REDUCED BY INHALATION OF RESPIRABLE CRYSTALLINE SILICA. ALSO LUNG SCARRING PRODUCED BY SUCH INHALATION MAY LEAD TO A PROGRESSIVE MASSIVE FIBROSIS OF THE LUNG WHICH MAY AGGRAVATE OTHER PULMONARY CONDITIONS AND DISEASES AND WHICH INCREASES SUSCEPTIBILITY TO PULMONARY TUBERCULOSIS. PROGRESSIVE FIBROSIS MAY BE ACCOMPANIED BY NIGHT HEART ENLARGEMENT, HEART FAILURE, AND PULMONARY FAILURE. SMOKING AGGRAVATES THE EFFECTS OF EXPOSURE.
 EMERGENCY AND FIRST AID PROCEDURES:
 FOR SAND IN EYES DURING DRY SAWING OR GRINDING OPERATIONS, IMMEDIATELY FLUSH GENEROUSLY WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. FOR GROSS INHALATION, REMOVE PERSON IMMEDIATELY TO FRESH AIR, GIVE ARTIFICIAL RESPIRATION AS NEEDED, SEEK MEDICAL ATTENTION AS NEEDED.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
 WHEN DRY SAWING OR GRINDING USE DUSTLESS SYSTEMS FOR HANDLING, STORAGE, AND CLEANUP SO THAT AIRBORNE DUST DOES NOT EXCEED THE PEL. USE ADEQUATE VENTILATION AND DUST EQUIPMENT. PRACTICE GOOD HOUSEKEEPING. DO NOT PERMIT DUST TO COLLECT ON WALLS, FLOORS, SILLS, LEDGES, MACHINERY OR EQUIPMENT. MAINTAIN CLEAN AND FIT TEST RESPIRATORS IN ACCORDANCE WITH OSHA REGULATIONS. MAINTAIN AND TEST VENTILATION AND DUST COLLECTION EQUIPMENT. WASH OR VACUUM CLOTHING WHICH HAS BECOME DUSTY. SEE ALSO CONTROL MEASURES IN SECTION VIII.
 WASTE DISPOSAL METHOD:
 NORMAL BREAKAGE MAY BE PICKED UP AND DISCARDED AS COMMON WASTE. RESIDUE FROM DRY SAWING AND GRINDING OPERATIONS SHOULD BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.
 PRECAUTIONS TO BETAKEN IN HANDLING AND STORING: NONE
 OTHER PRECAUTIONS:
 SEE OSHA HAZARD COMMUNICATION RULE 29 CFR SECTIONS 1910.1200, 1915.99, 1917.28, 1918.90, 1926.59 AND 1928.21, AND STATE AND LOCAL WORKER OR COMMUNITY "RIGHT TO KNOW" LAWS AND REGULATIONS. WE RECOMMEND THAT SMOKING BE PROHIBITED IN ALL AREAS WHERE RESPIRATORS MUST BE USED. WARN YOUR EMPLOYEES (AND YOUR CUSTOMERS-USERS IN CASE OF RESALE) BY POSTING AND OTHER MEANS OF THE HAZARD AND OSHA PRECAUTIONS TO BE USED. PROVIDE TRAINING FOR YOUR EMPLOYEES ABOUT THE OSHA PRECAUTIONS.
 SEE ALSO AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM) STANDARD PRACTICES E1132-86, "STANDARD PRACTICE FOR HEALTH REQUIREMENTS RELATING TO OCCUPATIONAL EXPOSURE TO QUARTZ DUST".

SECTION VII - CONTROL MEASURES

RESPIRATORY PROTECTION

THE FOLLOWING CHART SPECIFIES THE TYPE OF RESPIRATORS WHICH MAY PROVIDE RESPIRATORY PROTECTION FOR CRYSTALLINE SILICA.

CONDITION PARTICULATE CONCENTRATION	RESPIRATORY PROTECTION FOR CRYSTALLINE SILICA MINIMUM RESPIRATORY PROTECTION *
UP TO 5 x PEL	ANY DUST RESPIRATOR
UP TO 10 x PEL	ANY DUST RESPIRATOR, EXCEPT SINGLE-USE OR QUARTER-MASK RESPIRATOR ANY FUME RESPIRATOR OR HIGH EFFICIENCY PARTICULATE FILTER RESPIRATOR ANY SUPPLIED-AIR RESPIRATOR ANY SELF-CONTAINED BREATHING APPARATUS
UP TO 50 x PEL	A HIGH EFFICIENCY PARTICULATE FILTER RESPIRATOR WITH A FULL FACEPIECE ANY SUPPLIED-AIR RESPIRATOR WITH A FULL FACEPIECE, HELMET OR HOOD ANY SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE
UP TO 500 x PEL	A POWERED AIR-PURIFYING RESPIRATOR WITH A HIGH EFFICIENCY PARTICULATE FILTER A TYPE C AIR-PURIFYING RESPIRATOR OPERATOR IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE OR CONTINUOUS-FLOW MODE
GREATER THAN 500 x PEL OR ENTRY AND ESCAPE FROM UNKNOWN CONCENTRATIONS	SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE MODE A COMBINATION RESPIRATOR WHICH INCLUDES A TYPE C SUPPLIED-AIR RESPIRATOR WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE CONTINUOUS-FLOW MODE AND AN AUXILIARY SELF-CONTAINED BREATHING APPARATUS OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE.

* ONLY NIOSH-APPROVED OR MSHA-APPROVED EQUIPMENT SHOULD BE USED (SEE 29 CFR 1910.134)

SEE ALSO ANSI STANDARD Z88 2-1980 "PRACTICES FOR RESPIRATORY PROTECTION"

VENTILATION: LOCAL EXHAUST: WHEN DRY SAWING OR GRINDING CONCRETE MASONRY PRODUCTS, USE SUFFICIENT LOCAL EXHAUST TO REDUCE THE LEVEL OF RESPIRABLE DUST TO THE PEL. SEE ACGIH "INDUSTRIAL VENTILATION, A MANUAL OF RECOMMENDED PRACTICE", LATEST EDITION.
 MECHANICAL
 SEE "OTHER PRECAUTIONS" UNDER SECTION VII.
 SPECIAL
 SEE "OTHER PRECAUTIONS" UNDER SECTION VII.
 OTHER
 SEE "OTHER PRECAUTIONS" UNDER SECTION VII.
 PROTECTIVE GLOVES
 OPTIONAL
 EYE PROTECTION
 WHEN SAWING OR GRINDING CONCRETE MASONRY PRODUCTS WEAR PROTECTIVE OR TIGHT FITTING GOGGLES (SAFETY GLASSES).
 OTHER PROTECTIVE CLOTHING OR EQUIPMENT
 OPTIONAL
 WORK/HYGIENIC PRACTICES
 AVOID CREATING AND BREATHING DUST. SEE "OTHER PRECAUTIONS" UNDER SECTION VII.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION CONTAINED HEREIN. WE ACCEPT NO RESPONSIBILITY AND DISCLAIM ALL LIABILITY FOR ANY HARMFUL EFFECTS WHICH MAY BE CAUSED BY EXPOSURE TO AIRBORNE DUST PARTICLES CREATED BY DRY SAWING OR GRINDING OF OUR PRODUCTS. CUSTOMERS/USERS OF CONCRETE MASONRY PRODUCTS MUST COMPLY WITH ALL APPLICABLE HEALTH AND SAFETY LAWS, REGULATIONS AND ORDERS.